

Wellblech Stahl 27/111

Material	RAL-Farbe	Stärke mm	Welle 27/111 Stahl	mit Vlies
Stahl beidseitig verzinkt		0,60	√	
		0,75	√	
		0,88	√	
		1,00	√	
		1,25		
25 mμ/RSL	1014	0,75	√	
	1015		√	
	1019		√	
	3000		√	√
	3016		√	√
	6005		√	√
	6011		√	√
	7016		√	√
	7035		√	√
	8004		√	√
	8011		√	√
	8012		√	√
	9001		√	
	9002		√	√
	9006		√	√
35 mμ/RSL	rot-matt	0,75	√	
	hellbraun-matt		√	
25 mμ/RSL	7016	0,60	√	√
	8011		√	√
	8012		√	√
	8014		√	√
	9002		√	√
	9006		√	√
25 mμ/RSL	7016	0,88		
	8012		√	√
	9002		√	√
	9006		√	√
25 mμ/RSL	7016	1,00		
	8004			
	8011			
	8012		√	√
	9002		√	√
	9006		√	√
25 mμ/RSL	7016	1,25		
	8012			
	9002			
	9006			
25 mμ/RSL	8012	1,50		
	9002			
	9006			
15 mμ/RSL	9002	0,75		
		0,88		
		1,00		
		1,13		
		1,25		
		1,50		
15 mμ/RSL	9010	0,75		
		0,88		
		1,00		
		1,13		
		1,25		
		1,50		

RSL = Rückseite Schutzlack 12 mμ, ähnlich RAL 9002